

MASONRY SAW

TBE350★★


Cutting depth up to 110 mm



Swivelling saw head enables 45° mitre cuts



Two robust castors ensure total manoeuvrability in the deployment location



Angle stop provided for cuts of 30° to 90°

The TBE350** table saw offers an uncompromising price-performance ratio as well as high flexibility through numerous settings and application options. A sturdy saw table with an-

ti-slip support guarantees clean cuts. The swivelling saw head allows mitre cuts to be made with ease. Detachable table feet and transport wheels ensure trouble-free transport.

System & Accessories

Technical data

Saw blade	
Max. cutting depth	110 mm
Max. saw blade Ø	400 mm
Cutting length	600 mm
Saw blade speed	2800 rpm
Saw blade holder Ø	25.4 mm

Drive

Drive / motor	Electric
Output	2.2 kW
Standard voltage/frequency	230 V / 50 Hz
Optional voltage/frequency	110 V / 60 Hz
Engine cooling	Air cooling
Saw blade drive	Direct

Design

Infinitely adjustable cutting depths
Angle cutting function (angle stop)
Mitre cutting function
Cap cutting function
Water tank made from powder-coated steel
Electric water pump
Dismantable

Dimensions & Weight

Length	1140 mm
Width	640 mm
Height	1230 mm
Weight	79 kg

System & Accessories

Masonry TBE350**	
10981423	Masonry saw TBE350** / 230 V
10981424	Masonry saw TBE350** / 110 V