

TILE SAW

TRE250★★★

Cutting depth up to 60 mm



Cutting length up to 1 m for cutting large tiles



Clean cuts thanks to precise saw head guide and robust design



Safe and easy transport thanks to folding feet and transport wheels

The TRE250*** tile saw enables the cutting of various tile sizes and types to a cutting length of 1 m. A range of adjustment and application options ensure maximum flexibility. The

robust design and precise saw head guide guarantee a clean cut. Transport wheels and folding table feet facilitate transport and position at the location of use.

System & Accessories

Technical data

Saw blade	
Max. cutting depth	60 mm
Max. saw blade Ø	250 mm
Cutting length	940 mm (1050 mm)*
Saw blade speed	2800 rpm
Saw blade holder Ø	25.4 mm
* Plunge cut	

Drive

Drive / motor	Electric
Output	1.3 kW
Standard voltage/frequency	230 V / 50 Hz
Optional voltage/frequency	110 V / 60 Hz
Engine cooling	Air cooling
Saw blade drive	Direct

Design

Infinitely adjustable cutting depths
Angle cutting function (angle stop)
Mitre cutting function
Cap cutting function
Electric water pump
Folding legs

Dimensions & Weight

Length	1375 mm
Width	740 mm
Height	1275 mm
Weight	79 kg

System & Accessories

Tile saw TRE250***	
10989500	Tile saw TRE250*** / 230 V
10989100	Tile saw TRE250*** / 110 V

Accessories

10995459	Side splash guard
10995489	Parallel guide