
DRILL RIG

DRU160★★★

Core drilling up to Ø 160 mm



Precision work due to high quality support with sturdy roller guide



Universal field of application thanks to 90°-45° diagonal adjustment



Efficient drill rig set-up using a standard centre indicator

The DRU160*** is the lightweight among drill rigs up to Ø 160 mm. The standardised clamping collar system enables quick mounting of common drill motors. In addition, a centre indicator, angle indicator and

spirit level enhance user-friendliness and help save valuable time during drill rig set-up. The anchor or vacuum attachment facility also increase flexibility.

TYROLIT

System & Accessories

Technical data

Drill rig DRU160***	
Drill diameter range	15–160 mm
Max. drill diameter with water collecting ring	130 mm
Max. drill bit length	560 mm

Design

Aluminium dowel-vacuum foot
Feed using hand crank
Diagonal adjustment 90°-45°
Centre indicator
Angle indicator
Spirit level
Adjustable feet (M12)
Adjustable and interchangeable roller guides
2 handles
Clamping collar Ø 60 mm

Dimensions & Weight

Length	400 mm
Width	200 mm
Height	866 mm
Weight	9 kg

System recommendation

Core drilling system with DRU160***	
10987400	Drill rig DRU160***
10992077	El. drill motor DME20PW***
976014	Vacuum set
984035	Vacuum pump CV 45 l/min, 0.8 bar EU
975381	Vacuum hose 3 m complete

System & Accessories

Accessories	
976014	Vacuum set
984035	Vacuum pump CV 45 l/min, 0.8 bar EU
975372	Vacuum pump CV 45 l/min, 0.8 bar CH
975381	Vacuum hose 3 m complete
977394	Quick grip device 1.7 – 3.1 m
977448	Clamp for quick grip device; 1.7 – 3.1 m
977593	Fastening bolt assembly for vacuum base
977614	Fastening bolt assembly (masonry); for vacuum base
976136	Water retention ring complete Ø 70 mm
976134	Water retention ring complete Ø 130 mm
977437	Water retention ring holder; with centering device
977348	Gasket Ø 70 mm
976128	Gasket Ø 130 mm
974270	Extraction device for core bits
977353	Extraction device for cores
976616	Tool bag
10991465	Water tank 10 l