

---

# FLOOR SAW

## FSG513★★★

Cutting depth up to 170 mm



User-friendly cutting depth setting and convenient speed control



Optimised centre of gravity above the shaft



Universal field of application with left and right cutting function

Thanks to its extremely robust, high-quality chassis, the FSG513\*\*\* is highly robust and flexible thanks to the left- and right-handed as well

as corner flush cutting functions. The reliable Honda petrol engine is equipped with a cyclone air filter.

**TYROLIT**

---

# System & Accessories

## Saw blade

Saw blade	
Max. cutting depth	170 mm
Max. saw blade Ø	450 mm
Saw blade speed	2600 rpm
Saw blade uptake Ø	25.4 mm
Carrier Ø	11.5 mm
Reference circle Ø	57.4 mm

## Drive

Drive/motor	Petrol
Type	Honda
Power	8.2 kW / 11 HP
Fuel	Lead free
Fuel tank	6.1 l
Engine cooling	Air cooling
Feed	Manual
Blade drive	Via V-belt

## Design

Manual, cutting depth adjustment via spindle
Cutting depth indicator
Tool cooling using water fork
Left and right hand cutting function
Flush corner cut function
25 l water tank

## Dimensions & Weight

Length	1136 mm
Width	578 mm
Height	1016 mm
Weight	113 kg

## System & Accessories

Floor saw FSG513***	
10988800	Floor saw FSG513*** incl. water tank kit

  

Accessories	
10988783	Water tank kit (water tank holder, water tank, hook for transport)