

DRIVE AU

Working pressure up to 2000 bar



User-friendly thanks to clear inspection and control panel



Accessories: Distributor head for 8 pressing tools



Two separately adjustable outputs for controlled pressing work

Suitable for pressing tools CP110 and BTH350. The high-pressure drive generates a pressing force of up to 2100 tonnes.

System & Accessories

Technical data

Hydraulics	
Press force	0,5 l/min at 2000 bar
Low pressure	2.4 l/min at 150 bar
Booster pressure	14.4 l/min at 80 bar
Oil tank capacity	13 litres

Motor

Electric motor	Air-cooled
Voltage	200V / 230V / 380V / 400V / 460V
Current (400 V / 50 Hz)	10 A
Frequency	50 Hz / 60 Hz
Output	2.2 kW

Connections

High pressure	2 off (optionally 8 pcs.)
Low pressure	4 off (optionally 8 pcs.)

Dimensions & weight

Length	750 mm
Width	560 mm
Height	755 mm
Weight	127 kg

System & Accessories

Drive unit AU	
975754 *	High pressure drive unit AU 400/50 EU
975761	Tool box

Accessories

973071	El.-plug CEE 16/5pol.
974045	4-way HP adaptor unit
960827	2 way inlet connection
970300	Adaptor M24-G1/4" for SP
974053	Return nipple complete CP/SP
974054	Screw nipple complete CP/SP
974050	Screwing set CP/SP

* Different voltage types are available upon request.