

DRIVE PPH25RR ★★★

Output 25 kW



Freedom of movement thanks to remote control. All remote control functions are adjustable



Three-way switch, secondary connections, operating hours counter



Plastic cover can be removed without tools

The 4-stage control ensures optimal cutting speeds for all applications and the potentiometer of the remote

control ensures a wire-conserving smooth start/soft start.

System & Accessories



Technical data

Electric motor

Output	25 kW
--------	-------

Hydraulics

Pressure stages	4
2 feed circuits	Radial piston pump
Main circuit	Triple gear pump

Output

Stage 1	45 l/min at 230 bar
Stage 2	50 l/min at 200 bar
Stage 3	60 l/min at 170 bar
Stage 4	70 l/min at 140 bar

Electrical equipment

Voltage	380 V / 400 V / 480 V
Frequency	50 Hz / 60 HZ
Current consumption (400 V / 50 Hz)	42 A
2 secondary connections, (230 V / 50 Hz / 10 A (400 V / 50 Hz only)	

Dimensions

Length	760 mm
Width	550 mm
Height	1,140 mm
Weight	170 kg

System & Accessories

Drive unit PPH25RR***

10983900*	Drive unit PPH25RRP / 380-420V / 50Hz / Freq. 434MHz
976206	Hose package 5pieces 8 m FD
975672	Hose package 2pieces 8 m FF (feed)

Accessories

973074	El.-plug CEE 63/5pol.
--------	-----------------------

* Different voltage and frequency types are available upon request.