

DRIVE PPH40RR ★★★

Output 40 kW



Freedom of movement thanks to remote control. All remote control functions are adjustable



Three-way switch, secondary connections, operating hours counter



Plastic cover can be removed without tools

The 4-stage control ensures optimal cutting speeds for all applications and the potentiometer of the remote

control ensures a wire-conserving smooth start/soft start.

System & Accessories



Technical data

Electric motor

Output	40 kW
--------	-------

Hydraulics

Pressure stages	4
2 feed circuits	Radial piston pump
Main circuit	Triple gear pump

Output

Stage 1	65 l/min at 250 bar
Stage 2	75 l/min at 220 bar
Stage 3	80 l/min at 200 bar
Stage 4	90 l/min at 180 bar

Electrical equipment

Voltage	380 V / 400 V / 460 V / 575 V
Frequency	50 Hz / 60 Hz
Current consumption (400 V / 50 Hz)	60 A
2 secondary connections, 230 V / 50 Hz / 10 A (400 V / 50 Hz only)	

Dimensions

Length	820 mm
Width	560 mm
Height	1,260 mm
Weight	238 kg

System & Accessories

Drive unit PPH40RR***

10983400*	Drive unit PPH40RRP / 380-420V / 50Hz / Freq. 434MHz
975672	Hose package 2pieces 8 m FF (feed)
976207	Hose package 3pieces 8 m FD

Accessories

973074	El.-plug CEE 63/5pol.
--------	-----------------------

* Different voltage and frequency types are available upon request.