

MASONRY SAW

TME1000★★★

Cutting depth up to 380 mm



Large cutting depths to 380 mm possible (with saw blade Ø 1000 mm)



Precise mitre cutting due to mitre stop



Fork lift guides for easy and secure transport

The TME1000*** convinces through maximum stability and robustness. The precise stainless-steel saw table guide guarantees a clean cut. Construction-site suitable leading pulleys, forklift guides and a crane hook ensure trouble-free transport.

The intelligent blade guard construction enables quick and easy blade installation. Servicing requirements are reduced to a minimum due to low-maintenance saw blade drive via a transmission.

System & Accessories

Technical data

Saw blade	
Max. cutting depth	380 mm
Max. saw blade Ø	1000 mm
Cutting length	660 mm
Saw blade speed	910 rpm
Saw blade holder Ø	60 mm
Carrier Ø	11.5 mm
Reference circle Ø	120 mm

Drive

Drive/motor	Electric
Output	7.5 kW
Standard voltage/frequency	400 V / 50 Hz
Engine cooling	Air cooling
Saw blade drive	Via gears

Design

Infinitely adjustable cutting depths
Angle cutting function (angle stop)
Mitre cutting function
Transport hook and fork lift guides
Pull-out water tank
Electric water pump

Dimensions & Weight

Length	1800 mm
Width	1030 mm
Height	1500 mm
Weight	324 kg

System & Accessories

Masonry saw TME1000***	
10989800	Masonry saw TME1000*** / 400 V

Accessories

10978735	Mitre stop (Jolly table)
----------	--------------------------