

TILE SAW

TRE250★★★

Cutting depth up to 60 mm



Cutting length up to 1 m for cutting large tiles



Clean cuts thanks to precise saw head guide and robust design



Safe and easy transport thanks to folding feet and transport wheels

The TRE250*** tile saw enables the cutting of various tile sizes and types to a cutting length of 1 m. A range of adjustment and application options ensure maximum flexibility. The

robust design and precise saw head guide guarantee a clean cut. Transport wheels and folding table feet facilitate transport and position at the location of use.

System & Accessories

Technical data

| Saw blade | |
|--------------------|-------------------|
| Max. cutting depth | 60 mm |
| Max. saw blade Ø | 250 mm |
| Cutting length | 940 mm (1050 mm)* |
| Saw blade speed | 2800 rpm |
| Saw blade holder Ø | 25.4 mm |
| * Plunge cut | |

Drive

| | |
|----------------------------|---------------|
| Drive / motor | Electric |
| Output | 1.3 kW |
| Standard voltage/frequency | 230 V / 50 Hz |
| Optional voltage/frequency | 110 V / 60 Hz |
| Engine cooling | Air cooling |
| Saw blade drive | Direct |

Design

| |
|--------------------------------------|
| Infinitely adjustable cutting depths |
| Angle cutting function (angle stop) |
| Mitre cutting function |
| Cap cutting function |
| Electric water pump |
| Folding legs |

Dimensions & Weight

| | |
|--------|---------|
| Length | 1375 mm |
| Width | 740 mm |
| Height | 1275 mm |
| Weight | 79 kg |

System & Accessories

| Tile saw TRE250*** | |
|--------------------|----------------------------|
| 10989500 | Tile saw TRE250*** / 230 V |
| 10989100 | Tile saw TRE250*** / 110 V |

Accessories

| | |
|----------|-------------------|
| 10995459 | Side splash guard |
| 10995489 | Parallel guide |