

DRILL MOTOR **DME22SU★★**

Core drilling up to Ø 180 mm



Three-speed transmission for optimum rotational speeds



Dry drilling with the included M16 adapter



Comes in a handy transport case

The DME22SU** drill motor is ideal for electrical and installation work. It features a 3-speed transmission and variable speed setting with soft start.

Integrated overload cut-outs and the PRCD safety switch ensure safe working. Dry drilling is also possible with the included M16 adapter.

System & Accessories

Technical data

| Drill Motor DME 22SU** | | |
|-------------------------------|-----------------------------------|----------|
| Voltage/Frequency | 230 V / 50-60 Hz 110 V / 50-60 Hz | |
| Type no. | 10993027 | 10993028 |
| Drill diameter range | 20–180 mm | |
| Nominal power | 2.2 kW | |
| Nominal current | 9.5 A | 18 A |
| Load speed | 400/750/1550 rpm | |
| No load speed | 850/1650/3450 rpm | |
| Motor cooling | air | |
| Tool attachment (external) | 1 ¼" | |
| Tool attachment (internal) | ½" | |
| Operation | Hand-held / rig-based | |
| Application | Wet / dry | |
| Electronic overload cut-out | • | |
| Mechanical overload cut-out | • | |
| PRCD protection switch | • | |
| Drill rig attachment | Clamping collar 60 mm | |

Dimensions & Weight

| | |
|--------|--------|
| Length | 552 mm |
| Width | 110 mm |
| Height | 150 mm |
| Weight | 6.0 kg |

System & Accessories

| Core drilling system with DRU160*** Drill rig | |
|--|---------------------------|
| 10993027 | El. Drill motor DME22SU** |
| 10987400 | Drill rig DRU160*** |
| 977619 | Fastening bolt assembly |

Accessories

| | |
|----------|-------------------------|
| 400439 | Extension 1/2" 100 mm |
| 359475 | Extension 1/2" 200 mm |
| 359476 | Extension 1/2" 300 mm |
| 889232 | Extension 1/2" 400 mm |
| 707230 | Extension 1/2" 500 mm |
| 378198 | Extension 1 1/4" 100 mm |
| 359471 | Extension 1 1/4" 200 mm |
| 359472 | Extension 1 1/4" 300 mm |
| 359473 | Extension 1 1/4" 400 mm |
| 359474 | Extension 1 1/4" 500 mm |
| 10983964 | Dust vacuum adaptor M16 |
| 10983845 | Centering spike 140 mm |
| 10986189 | Centering spike 233 mm |
| 10986190 | Strap wrench |